



Тел.: +996 555771513,  
email: info@ravenol.kg

## RAVENOL Calibration Fluid

**RAVENOL Calibration Fluid** is a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

### Application Notes

**RAVENOL Calibration Fluid V** is used as a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

### Quality Classifications

**RAVENOL Calibration Fluid** is tried and tested for aggregates specifying:

### Specifications

ISO 4113, SAE J 967D, MB 133.0

### Characteristic

**RAVENOL Calibration Fluid** offers:

- Excellent wear protection
- Excellent corrosion protect
- Low tendency to foam

**RAVENOL Calibration Fluid** is a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

### Application Notes

**RAVENOL Calibration Fluid V** is used as a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal

preservation of fuel systems.

## Quality Classifications

**RAVENOL Calibration Fluid** is tried and tested for aggregates specifying:

### Specifications

ISO 4113, SAE J 967D, MB 133.0

### Characteristic

**RAVENOL Calibration Fluid** offers:

- Excellent wear protection
- Excellent corrosion protect
- Low tendency to foam

Characteristics	Unit	Data	Audit
Colour		farblos	visual
Density at 20°C	kg/m <sup>3</sup>	826	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	2,62	DIN 51 562
Flash point (COC)	°C	90	DIN ISO 2592
Pourpoint	°C	-40	DIN ISO 3016
TBN base number	mg KOH/g	2,5	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.