



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Getriebeöl CLP 68

RAVENOL Getriebeöl CLP 68 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity. **RAVENOL Getriebeöl CLP 68** has a low pour point and therefore a very good cold behaviour.

Application Notes

RAVENOL Getriebeöl CLP 68 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeöl CLP 68 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Characteristic

RAVENOL Getriebeöl CLP 68 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.

RAVENOL Getriebeöl CLP 68 is a high quality, mineral-based gear oil

formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity. **RAVENOL Getriebeöl CLP 68** has a low pour point and therefore a very good cold behaviour.

Application Notes

RAVENOL Getriebeöl CLP 68 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeöl CLP 68 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Characteristic

RAVENOL Getriebeöl CLP 68 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	879	EN ISO 12185
Viscosity at 40°C	mm ² /s	67,0	DIN 51 562
Viscosity at 100°C	mm ² /s	8,6	DIN 51 562
Viscosity index VI		100	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592

Characteristics	Unit	Data	Audit
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.