



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Getriebeoel Glycosynth Gear 150

RAVENOL Getriebeoel Glycosynth Gear 150 is a synthetic industrial gear oil based on poly-alkylene-glycol under addition of special additives.

RAVENOL Getriebeoel Glycosynth Gear 150 is suitable for the lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load.

Application Notes

RAVENOL Getriebeoel Glycosynth Gear 150 is very suitable for the lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load. In comparison with mineral industrial gear oils a substantial extension of the oil drain interval is possible. **RAVENOL Getriebeoel Glycosynth Gear 150** may not be contacted with aluminium and aluminiumalloys.

Specifications

DIN 51 517 Part 3, FZG>12

Characteristic

RAVENOL Getriebeoel Glycosynth Gear 150 offers:

- a natural high viscosity index
- excellent high and low temperature properties
- a very good resistance towards high pressures and shock loads
- a high resistance against oxidation
- a long service life

RAVENOL Getriebeoel Glycosynth Gear 150 is a synthetic industrial gear oil based on poly-alkylene-glycol under addition of special additives.

RAVENOL Getriebeoel Glycosynth Gear 150 is suitable for the

lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load.

Application Notes

RAVENOL Getriebeoel Glycosynth Gear 150 is very suitable for the lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load. In comparison with mineral industrial gear oils a substantial extension of the oil drain interval is possible. **RAVENOL Getriebeoel Glycosynth Gear 150** may not be contacted with aluminium and aluminium alloys.

Specifications

DIN 51 517 Part 3, FZG>12

Characteristic

RAVENOL Getriebeoel Glycosynth Gear 150 offers:

- a natural high viscosity index
- excellent high and low temperature properties
- a very good resistance towards high pressures and shock loads
- a high resistance against oxidation
- a long service life

Characteristics	Unit	Data	Audit
Colour		colourless	visual
Density at 20°C	kg/m ³	1073	EN ISO 12185
Viscosity at 40°C	mm ² /s	140,0	DIN 51 562
Viscosity at 100°C	mm ² /s	22,4	DIN 51 562
Viscosity index VI		189	DIN ISO 2909
Flash point (COC)	°C	268	DIN ISO 2592
Pourpoint	°C	- 42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.