



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Getriebeoel Glycosynth Gear 320

RAVENOL Getriebeoel Glycosynth Gear 320 is synthetic industrial gear oil based on poly-alkylene-glycol under addition of special additives.

RAVENOL Getriebeoel Glycosynth Gear 320 is suitable for the lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load.

Application Notes

RAVENOL Getriebeoel Glycosynth Gear 320 is very suitable for the lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load. In comparison with mineral industrial gear oils a substantial extension of the oil drain interval is possible.

RAVENOL Getriebeoel Glycosynth Gear 320 may not be contacted with aluminium and aluminium alloys.

Specifications

DIN 51 517 Teil 3 CLP, FZG >12

Characteristic

RAVENOL Getriebeoel Glycosynth Gear 320 offers:

- a natural high viscosity index
- a low pour point
- excellent high and low temperature properties
- a very good resistance towards high pressures and shock loads
- a high resistance against oxidation
- a long service life
- a strong reduction of wear

RAVENOL Getriebeoel Glycosynth Gear 320 is synthetic industrial gear oil based on poly-alkylene-glycol under addition of special additives.

RAVENOL Getriebeoel Glycosynth Gear 320 is suitable for the

lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load.

Application Notes

RAVENOL Getriebeoel Glycosynth Gear 320 is very suitable for the lubrication of heavy loaded mechanical gearboxes and bearings with a high thermal load. In comparison with mineral industrial gear oils a substantial extension of the oil drain interval is possible.

RAVENOL Getriebeoel Glycosynth Gear 320 may not be contacted with aluminium and aluminium alloys.

Specifications

DIN 51 517 Teil 3 CLP, FZG >12

Characteristic

RAVENOL Getriebeoel Glycosynth Gear 320 offers:

- a natural high viscosity index
- a low pour point
- excellent high and low temperature properties
- a very good resistance towards high pressures and shock loads
- a high resistance against oxidation
- a long service life
- a strong reduction of wear

Characteristics	Unit	Data	Audit
Colour		farblos	visual
Density at 20°C	kg/m ³	1066	EN ISO 12185
Viscosity at 40°C	mm ² /s	320,0	DIN 51 562
Viscosity at 100°C	mm ² /s	52,7	DIN 51 562
Viscosity index VI		231	DIN ISO 2909
Flash point (COC)	°C	268	DIN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.