



Тел.: +996 555771513,  
email: info@ravenol.kg

## **RAVENOL LGC - Protect C13 HOT CLIMATE - 15°C**

**BASED ON GLYCERIN**  **IN** image not found, type unknown

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** is a ready to use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant with glycerine additive for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining glycerine and silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** protects the cooling system from rust, frost, and in summer, from overheating.

### **Application Notes**

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** to radiator to fill line.

### **Quality Classifications**

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** is tried and tested for aggregates specifying:

## Specifications

VW TL 774-J (acc. to G13 ), Volkswagen VW G013A8JM1, G013A8JM8, G013A8JM9, Audi, Skoda & Seat

## Characteristic

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** offers:

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

clear.gif

**BASED ON GLYCERIN** Image not found or type unknown

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** is a ready to use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant with glycerine additive for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining glycerine and silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** protects the cooling system from rust, frost, and in summer, from overheating.

## Application Notes

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** is a prediluted coolant with frost and rust protection for year-round use in

automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** to radiator to fill line.

## Quality Classifications

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** is tried and tested for aggregates specifying:

## Specifications

VW TL 774-J (acc. to G13 ), Volkswagen VW G013A8JM1, G013A8JM8, G013A8JM9, Audi, Skoda & Seat

## Characteristic

**RAVENOL LGC Lobrid Glycerin Coolant HOT CLIMATE -15°C** offers:

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

Characteristics	Unit	Data	Audit
Colour		violett / lila	visual
Density at 20°C	kg/m <sup>3</sup>	1050	EN ISO 12185
pH- value		7,8	ASTM D 1287
Freezing point	°C	-15	ASTM D 1177

All indicated data are approximate values and are subject to the commercial fluctuations.