



Тел.: +996 555771513,  
email: info@ravenol.kg

## **RAVENOL LGC Lobrid Glycerin Coolant COLD CLIMATE -60°C**

**RAVENOL LGC COLD CLIMATE -60° C** is a ready to use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant with glycerine additive for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining glycerine and silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL LGC COLD CLIMATE -60°C** protects the cooling system from rust, frost, and in summer, from overheating.

### **Application Notes**

**RAVENOL LGC COLD CLIMATE -60°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

**Instructions:** Add **RAVENOL LGC COLD CLIMATE -60°C** to radiator to fill line.

### **Approvals**

Freigabe (für Konzentrat): VW TL 774, Ausführung J

## **Practice and tested in aggregates with filling**

Volkswagen VW G013A8JM1, G013A8JM8, G013A8JM9, Audi, Skoda & Seat

## **Characteristic**

**RAVENOL LGC COLD CLIMATE -60°C** offers:

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

**RAVENOL LGC COLD CLIMATE -60° C** is a ready to use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant with glycerine additive for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining glycerine and silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL LGC COLD CLIMATE -60°C** protects the cooling system from rust, frost, and in summer, from overheating.

## **Application Notes**

**RAVENOL LGC COLD CLIMATE -60°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

**Instructions:** Add **RAVENOL LGC COLD CLIMATE -60°C** to radiator to fill line.

## Approvals

Freigabe (für Konzentrat): VW TL 774, Ausführung J

## Practice and tested in aggregates with filling

Volkswagen VW G013A8JM1, G013A8JM8, G013A8JM9, Audi, Skoda & Seat

## Characteristic

**RAVENOL LGC COLD CLIMATE -60°C** offers:

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

Characteristics	Unit	Data	Audit
Colour		violett/lila	visual
Density at 20°C	kg/m <sup>3</sup>	1113	EN ISO 12185
pH-value (50 %, 20°C)		8,0	ASTM D 1287
Freezing point (50 %-Lösung)	°C	-60	ASTM D 1177

All indicated data are approximate values and are subject to the commercial fluctuations.