

RAVENOL Frostlube F 12

Synthetic



20 L

Հողված:

1323350-020

Հողված:

1323350-020-01-999



20 L ecobox

Հողված:

1323350-B20



60 L

Հողված:

1323350-060



208 L

Հողված:

1323350-208

RAVENOL Frostlube F 12 is designed on the basis of specially selected base oils for the low-temperature performance and high quality hydraulic additives including corrosion and oxidation inhibitors as well as additives for the reduction of wear and foaming.

RAVENOL Frostlube F 12 is a high quality, anti-wear hydraulic oil with a very high viscosity index, good shear stability and excellent low-temperature properties.

Application Note

RAVENOL Frostlube F 12 is excellently suitable for application in extremely low temperatures, e.g. equipment in refrigerated warehouses or mobile facilities, which are used outdoors under extreme winter conditions.

RAVENOL Frostlube F 12 is specifically formulated so that a consistent viscosity is extensively given even in the case of extremely varying temperatures.

RAVENOL Frostlube F 12 is a shear stable, high quality hydraulic oil and therefore, suitable for application under extreme hydraulic conditions without risk for the system. If the oil temperature is permanently above 80°C, the hydraulic system should be pressurised to minimise oil loss due to evaporation.

Characteristics

- An extremely high viscosity index so that the good lubrication properties and the protection in the event of minimal viscosity alterationss are ensured by a wide temperature range.
- A low pour point; therefore, application at extremely low temperatures is permitted without the risk of freezing.
- An extremely good resistance to oxidation and a very good shear stability; therefore, longer service life of the oil under the usually extreme application conditions.
- Protection of the hydraulic system against corrosive influences.
- Anti-wear effect.
- Load bearing capability.
- Longer service life of the oil.

Բնութագրերը

Անուն	Իմաստը	Առաջին
Համապատասխանում է արտադրողի բնութագրերին	ISO 6743-4 HV	
Հատուկ հզորություն 20°C-ի դեպքում	828 q/սմ³	EN ISO 12185
Գույն	Green	տեսողական
Մածուցիկություն 100 °C-ում	6.7 mm²/s	DIN 51562-1
Մածուցիկություն 40 °C-ում	19.9 mm²/s	DIN 51562-1
Մածուցիկության ինդեքս VI	332	DIN ISO 2909
Բյուրեղացման ջերմաստիճան	-49 °C	DIN ISO 3016
Կառուցման ջերմաստիճան	172 °C	DIN EN ISO 2592

Դադարեցված փաթեթավորում

Փաթեթավորում	Հողված	Ծորիխ կող
60 լ	1323350-060-01-999	
208 լ	1323350-208-01-999	